



- | ITEM | DESCRIPTION  |
|------|--|
| 1.   | ACTUATOR (LOCATION MAY VARY)                       |
| 2.   | DAMPER FRAME                                       |
| 3.   | TRUSS, STL. OR PFL.                                |
| 4.   | SLEEVE   |
| 5.   | OVER CENTER LOCK                                   |
| 6.   | MOUNTING ANGLES 1 1/2" X 1 1/2" 16 GA MIN          |
| 7.   | JOINT, SLEEVE TO DUCT-BREAK AWAY CONNECTIONS       |
| 8.   | CALLING MATERIAL                                   |
| 9.   | STEEL OR WOOD STUD CONSTRUCTION (SINGLE STUD ONLY) |


- | ITEM | DESCRIPTION                                   |
|------|---|
| 1.   | ACTUATOR (LOCATION MAY VARY)                  |
| 2.   | DAMPER FRAME                                  |
| 3.   | TRUSS, STL. OR PFL.                           |
| 4.   | SLEEVE  |
| 5.   | OVER CENTER LOCK                              |
| 6.   | MOUNTING ANGLES 1" X 2 1/2" 16 GA MIN         |
| 7.   | MOUNTING ANGLES 1 1/2" X 1 1/2" 16 GA MIN     |
| 8.   | JOINT, SLEEVE TO DUCT-BREAK AWAY CONNECTIONS  |
| 9.   | CALLING MATERIAL                              |
| 10.  | GRILLE/DIFFUSER                               |
| 11.  | STEEL OR WOOD CONSTRUCTION (SINGLE STUD ONLY) |
| 12.  | STEEL CONSTRUCTION ONLY                       |



FSD36/37-C1  
CEILING PARTITION  
WITH DUCT DROP



FSD36/37-C2  
CEILING PARTITION  
WITH V-FRAME DIFFUSER



FSD36/37-C3  
CEILING PARTITION  
WITH FLAT FRAME DIFFUSER  
STEEL STUD CONSTRUCTION ONLY




FIG. 1 ACTUATOR ABOVE DAMPER IN DUCT-DROP




FIG. 3 ACTUATOR ABOVE DAMPER WITH V-FRAME DIFFUSER




FIG. 5 ACTUATOR ABOVE DAMPER WITH FLAT-FRAME DIFFUSER




FIG. 2 ACTUATOR BELOW DAMPER, IN DUCT DROP




FIG. 4 ACTUATOR BELOW DAMPER WITH V-FRAME DIFFUSER




FIG. 6 ACTUATOR BELOW DAMPER WITH FLAT-FRAME DIFFUSER

